




ALLINEATORI A CINGHIA / STRAP CLAMPS

AL 4090 C – AL 4180 C – AL 4250 C- AL 4400 C – AL 4500 C



AL 4090 C



AL 4180 C



AL 4250 C



AL 4400 C



AL 4500 C

CARATTERISTICHE TECNICHE	AL 4090 C	AL 4180 C	AL 4250 C	AL 4400 C	AL 4500 C	TECHNICAL SPECIFICATIONS
Campo d'impiego	20÷90 mm	40÷180 mm	50÷250 mm	90÷400 mm	125÷500 mm	Working range
Regolazioni	Manicotti, Gomiti 45° e 90° e Tees <i>Couplers, 45° and 90° elbows and Tees</i>	Manicotti, Gomiti 45° e 90° e Tees <i>Couplers, 45° and 90° elbows and Tees</i>	Manicotti, Gomiti 45° e 90° e Tees <i>Couplers, 45° and 90° elbows and Tees</i>	Manicotti, Gomiti 45° e 90° e Tees <i>Couplers, 45° and 90° elbows and Tees</i>	Manicotti, Gomiti 45-90° <i>Couplers, Elbows 45-90°</i>	Applications
Set riduzioni	Non necessarie / Unecessary	Non necessarie / Unecessary	Non necessarie / Unecessary	Non necessarie / Unecessary	Non necessarie / Unecessary	Kit reducing rings
Dimensioni	800 x 550 x 80 mm	1200 x 250 x 155 mm	1500 x 250 x 160 mm	1900 x 420 x 300 mm	1300 x 700 x 500 mm	Dimensions
Peso	9 Kg	15 Kg	17 Kg	26 Kg	21 Kg	Weight
Accessori di serie	Cassa in legno <i>Wooden case</i>	Cassa in legno <i>Wooden case</i>	Cassa in legno <i>Wooden case</i>	-	-	Standard accessories
Accessori a richiesta	-	-	-	Terzo braccio AL/D 4400 C idoneo per figure a Tees <i>Tees application</i> AL/D 4400 C	-	Accessories on request