



ALLINEATORI / ALIGNERS

AL 4063 R – AL 4125 R – AL 4225 R



AL 4063 R



AL 4125 R + AL/D 4125 R



AL 4225 R

CARATTERISTICHE TECNICHE	AL 4063 R	AL 4125 R	AL 4225 R	TECHNICAL SPECIFICATIONS
Campo d'impiego	20÷63 mm	20÷125 mm	50÷225 mm	Working range
Applicazioni	Manicotti, Gomiti 45° e 90° e riduzioni <i>Couplers, 45° and 90° elbows and reducers</i>	Manicotti, Gomiti 45° e 90° e riduzioni <i>Couplers, 45° and 90° elbows and reducers</i>	Manicotti, Gomiti 45° e 90° e riduzioni <i>Couplers, 45° and 90° elbows and reducers</i>	Applications
Set riduzioni	Incluse / included	Incluse / included	Incluse / included	Kit reducing rings
Dimensioni	510 x 160 x 140 mm	660 x 260 x 210 mm	790 x 360 x 330 mm	Dimensions
Peso	7 Kg	9 Kg	19 Kg	Weight
Accessori di serie	-	-	-	Standard accessories
Accessori a richiesta	Terzo braccio AL/D 4063 R idoneo per figure a Tees <i>Tees application AL/D 4063R</i>	Terzo braccio AL/D 4125 R idoneo per figure a Tees <i>Tees application AL/D 4125 R</i>	Terzo braccio AL/D 4225 R idoneo per figure a Tees <i>Tees application AL/D 4225 R</i>	Accessories on request