

SQUEEZE OFF UNIT mod. SCH 250 WORKING RANGE 160 ÷ 250 mm

DESCRIPTION

Squeeze off unit for PE pipes with 4 squeeze off points having a working range $180 \div 250$ mm.

"A" frame design of the painted steel squeeze off point incorporating an hydraulic cylinder and having handles enabling an easy transportation. Supplied with a manual hydraulic handpump.

Available on request with power unit drive with pneumatic input and hydraulic output powered by an aircompressor (not included in the supply).


Dimensions / Weights

Manual hydraulic handpump Power Unit Drive (on request) Squeeze off point (unit) 450 x 165 x 120 mm Weight 8,5 Kg 610 x 480 x 340 mm Weight 39 Kg 430 x 180 x 690 mm Weight 38 Kg

Details of the supply

- Hydraulic handpump with connection pipes (Power unit drive, on request)
- 4 squeeze off points complete with :
 - Hydraulic cylinder
 - End gauges set for 2 diameters/SDR
 - (1 set for 2 diameters/SDR by choice standard in the supply)
 - Wooden transport case

Further end gauges sets for SDR 11-17 are available on request.



Power unit drive with pneumatic input and hydraulic output



ıvıanuaı nyorallıc nanopump



Squeeze Off unit